

## BRANER 76 SLITTING LINE

0.012 - 0.190" Gauge Range  
 70,000 lb. Coil Max  
 Maximum Coil Width 79"  
 Slitting Widths 1.000" - 76.000"  
 20" and 24" ID  
 Material Types: HR, CR, PO, GALV

PRODUCT DATA		
COIL WEIGHT, MAX		70,000 lb (31,752 kg)
NUMBER OF MULTS, MAX		30
GAUGE		0.010 – 0.187 in. (0.25 – 4.75 mm)
WIDTH		76 in. (1930 mm) yield
DIAMETER	OUTER (OD), ENTRY, MAX	74 in. (1880 mm)
	OUTER (OD), EXIT, MAX	72 in. (1829 mm)
	INNER (ID), ENTRY	20 – 30 in. (508 – 762 mm)
	INNER (ID), EXIT	20 – 24 in. (508 – 610 mm)

## BRANER 36 SLITTING LINE

0.071 - 0.380" Gauge Range  
 45,000 lb. Coil Max  
 Maximum Coil Width 39"  
 Slitting Widths 0.750" - 36.000"  
 20" and 24" ID  
 Material Types: HR, CR, PO

PRODUCT DATA		
COIL WEIGHT, MAX		45,000 lb (20,412 kg)
NUMBER OF MULTS, MAX		31
GAUGE		0.024 – 0.375 in. (0.61 – 9.53 mm)
WIDTH		36 in. (914 mm) yield
DIAMETER	OUTER (OD), ENTRY, MAX	84 in. (2134 mm)
	OUTER (OD), EXIT, MAX	72 in. (1828 mm)
	INNER (ID), ENTRY	20 – 30 in. (508 – 762 mm)
	INNER (ID), EXIT	20 – 24 in. (508 – 610 mm)

## STAMCO SLITTING LINE

0.085 - 0.380" Gauge Range  
 80,000 lb. Coil Max  
 Maximum Coil Width 76.5"  
 Slitting Widths 2.000" - 72.000"  
 20" and 24" ID  
 Material Types: HR, CR, PO

PRODUCT DATA		
COIL WEIGHT, MAX		80,000 lb (36,287 kg)
NUMBER OF MULTS, MAX		25
GAUGE		0.040 – 0.375 in. (1.02 – 9.53 mm)
WIDTH		72 in. (1829 mm) yield
DIAMETER	OUTER (OD), ENTRY, MAX	84 in. (2134 mm)
	OUTER (OD), EXIT, MAX	76 in. (1930 mm)
	INNER (ID), ENTRY	20 – 30 in. (508 – 762 mm)
	INNER (ID), EXIT	20 – 24 in. (508 – 610 mm)



## RED BUD .500" SLITTER

Material Thickness: 0.050" – 0.500"

Width Capabilities:

Incoming Master Coil: 34" – 94"

Slit Width: 1.5" – 90"

Max OD: 94"

Entry OD: 30" – 92"

Exit OD: 30" – 92"

Entry ID: 20" – 40"

Exit ID: 20" – 24"

Max Coil Weight: 105,000 lbs



Gauge	50,000 tensile	75,000 tensile	100,000 tensile
0.050-0.100	34 cuts	34 cuts	34 cuts
0.140	34 cuts	34 cuts	24 cuts
0.160	34 cuts	30 cuts	22 cuts
0.180	34 cuts	27 cuts	20 cuts
0.200	34 cuts	24 cuts	17 cuts
0.220	33 cuts	22 cuts	16 cuts
0.240	28 cuts	20 cuts	14 cuts
0.260	24 cuts	18 cuts	12 cuts
0.280	21 cuts	16 cuts	12 cuts
0.300	17 cuts	14 cuts	10 cuts
0.320	15 cuts	12 cuts	9 cuts
0.340	13 cuts	11 cuts	8 cuts
0.360	12 cuts	10 cuts	7 cuts
0.380	11 cuts	9 cuts	6 cuts
0.400	10 cuts	8 cuts	5 cuts
0.420	9 cuts	7 cuts	4 cuts
0.440	8 cuts	6 cuts	3 cuts
0.460	8 cuts	5 cuts	3 cuts
0.480	7 cuts	4 cuts	3 cuts
0.500	6 cuts	3 cuts	2 cuts

## BRANER 78 SLITTER

Material Thickness: 0.020" – 0.250"

Width Capabilities:

Incoming Master Coil: 20" – 78"

Slit Width: 0.75" – 76"

Max OD: 78"

Entry OD: 30" – 80"

Exit OD: 30" – 80"

Entry ID: 20" – 32"

Exit ID: 20" – 24"

Max Coil Weight: 80,000 lbs

Gauge	50,000 tensile	75,000 tensile	100,000 tensile
0.020	32 cuts	32 cuts	26 cuts
0.036	32 cuts	32 cuts	24 cuts
0.048	32 cuts	30 cuts	21 cuts
0.062	32 cuts	27 cuts	18 cuts
0.075	32 cuts	24 cuts	17 cuts
0.090	28 cuts	22 cuts	15 cuts
0.135	22 cuts	16 cuts	13 cuts
0.150	18 cuts	13 cuts	N/A
0.187	11 cuts	8 cuts	N/A
0.250	6 cuts	4 cuts	N/A

